



Stellriemen




mit rundem Kopf, Nut und Kamm

100/20/5 cm	24 kg		6.50/St.
100/25/5 cm	29 kg	(braun + 2.-)	6.80/St.
100/30/5 cm	35 kg		7.-/St.
90° 30/5 cm	R = 25 cm		12.-/St.
30/5 cm	Ecken		12.-/St.



gerade mit Fase ohne Nut und Kamm

100/25/6 cm	35 kg		8.50/St.
100/30/6 cm	39 kg	(anthr. + 6.-)	9.-/St.
100/20/8 cm	38 kg		8.-/St.
100/25/8 cm	48 kg	(braun + 2.-)	8.50/St.
100/30/8 cm	58 kg		9.-/St.
100/40/8 cm	73 kg		15.50/St.
100/50/8 cm	95 kg		36.-/St.
100/30/10 cm	66 kg		15.-/St.



gerade beidseitig abgefast gegossen

100/30/4 cm	30 kg		24.-/St.
100/40/4 cm	40 kg		28.-/St.
100/30/6 cm	45 kg		32.-/St.
100/40/6 cm	60 kg		36.-/St.
100/50/6 cm	72 kg		52.-/St.
100/30/8 cm	60 kg		38.-/St.
100/30/10 cm	75 kg		48.-/St.
■ 100/40/10 cm	100 kg		52.-/St.
100/30/12 cm	90 kg		63.-/St.
100/48/12 cm	114 kg		75.-/St.

Gummi-Stellriemen



100/30/6 cm	36 kg schwarz		64.-/St.
-------------	---------------	--	-----------------

Granit- und Porphy-Stellriemen finden Sie auf Seite 59 + 63